

Delayed Mode Quality Control of Argo Float

WMO 6901245 - WMO 6901251

by

A. Gallo and G. Notarstefano

Approved for release by:

Dr. Cosimo Solidoro Director, Department of Oceanography



Contents

1	Introduction WMO 6901245 Float	3
2	Quality Check of Argo WMO 6901245 Float Data	
	2.2 Satellite Altimeter Report	
	2.3 Time Series of Argo Float Temperature and Salinity	
	2.4 Comparison Between Argo Float and Climatology	
3	Correction of WMO 6901245 Float Salinity Data	13
	3.1 Comparison between Argo Float and CTD Climatology	
	3.1.1 Configurations	
	3.1.2 Results	
1	Summary WMO 6901245 Float	21
4	Summary WIVIO 6901245 FIOat	∠⊥
5	Introduction WMO 6901251 Float	22
6	Quality Check of Argo WMO 6901251 Float Data	23
	6.1 Verification of Real-time Mode QC flags	23
	6.3 Time Series of Argo Float Temperature and Salinity	24
	6.4 Comparison Between Argo Float and Climatology	26
7	Correction of WMO 6901251 Float Salinity Data	32
	7.1.1 Comparison between Argo Float and CTD Climatology	32
	7.1.1 Configurations	32
	7.1.2 Results	33
8	Comparison between Argo float under study and other Argo float in the same area	40
9	Summary	42
10	References	42



1 Introduction WMO 6901245 Float

This report includes the delayed mode analysis performed for float 6901245. It was deployed in Mediterranean Sea (Catalan sub-basins) in November 2014 and after performed 288 cycles died. Before the analysis, real-time QC flags were visually inspected. The list of flags applied is QC=1 to all cycles. Then, the satellite altimeter comparison plot between the sea surface height and dynamic height anomaly, constructed for this float by Ifremer, was analyzed. Plots of temperature and salinity time series and plots of temperature, salinity and density plotted against the nearby historical CTD profiles was generated. This visual analysis can help in detecting sensor salinity anomalies and spikes.

The reference dataset used is composed of the following CTD and Argo historical datasets:


CTD:

- CMEMS: INSITU_MED_TS_REP_OBSERVATIONS_013_041
- Coriolis: CTD_for_DMQC_2018V01
- Historical CTD profiles provided through personal contact

Argo:

ARGO_for_DMQC_2018V01

Float 6901245 is the Arvor float where the pressure sensor is auto corrected and no adjustment is required. The OWC was run to estimate a salinity offset and a salinity drift (Cabanes et al., 2016).





2 Quality Check of Argo WMO 6901245 Float Data

2.1 Verification of Real-time Mode QC flags

The list of flags applied to the float in real-time mode is as follows.

Cycle number:

1-288 PSAL QC=1

2.2 Satellite Altimeter Report




Figure 1: Float 6901245. The comparison between the sea surface height (SSH) from the satellite altimetry and dynamic height anomaly (DHA) extracted from the Argo float temperature and salinity. The figure is created by the CLS/Coriolis and distributed by Ifremer (ftp://ftp.ifremer.fr/ifremer/argo/etc/argo-ast9-item13-AltimeterComparison/figures/).



2.3 Time Series of Argo Float Temperature and Salinity




Figure 2: Float 6901245. Time series of Argo float potential temperature (°C) on the left, and potential temperature profiles color-coded per cycle number on the right.




Figure 3: Float 6901245. Time series of Argo float potential salinity (PSS-78) on the left, and salinity profiles color-coded per cycle number on the right.

Before running the Owens and Wong method, referred to as OW hereafter, the theta-salinity (θ -S) diagram of the float is analyzed (Figure 4) and in particular the area where the θ -S relationship is the tightest (Figure 5). A very small salinity offset/drift is observed.






Figure 4: Float 6901245. θ -S diagram color-coded per cycle number.




Figure 5: Float 6901245. Area of the θ -S diagram (color-coded per cycle number) where the θ -S relationship is more uniform.



2.4 Comparison Between Argo Float and Climatology

Three salinity float profiles are selected to perform a comparison (in time and space) with the historical data. In figure 6, 7 and 8 each selected profile is compared with all reference data used in this analysis. The salinity float profile is depicted in black while other colors represent the salinity reference profiles. The red color means that the historical data are more recent with respect to the float ones, while magenta states that the float data are more recent than the historical ones (the maximal difference is 9 years). A time difference between 3 and 6, 6 and 9 and larger than 9 years is depicted in green, cyan and blue, respectively.




Figure 6: Float 6901245. Locations of the salinity float profile number 1 and historical CTD data (right panel) and the respective salinity profiles (left panel).




Figure 7: Float 6901245. Locations of the salinity float profile number 100 and historical CTD data (right panel) and the respective salinity profiles (left panel).






Figure 8: Float 6901245. Locations of the salinity float profile number 248 and historical CTD data (right panel) and the respective salinity profiles (left panel).

The comparison of these 3 selected salinity float profiles with the closest (in space and time) salinity reference profile in shown in Figures from 9 to 11. The agreement between the selected float salinity profiles and the historical salinity profiles is good in the intermediate layers where the comparison is useful for profiles 1 and 100. Figure 11 shows a small drift for profile 248 and the historical salinity profile.






Figure 9: Float 6901245. The salinity float profile number 1 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 10: Float 6901245. The salinity float profile number 100 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 11: Float 6901245. The salinity float profile number 248 (black dots) are compared to the nearest in space (top) and in time (botton) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 12: Float 6901245. T/S diagram plotted with and data from WMO boxes of CTD reference data +/- 10° of latitude and longitude. The black and blue cycles indicate the first and the last Argo profile, respectively. Green symbols represent other Argo profiles from this float. The thin colours lines indicate the reference data.



3 Correction of WMO 6901245 Float Salinity Data

3.1 Comparison between Argo Float and CTD Climatology

3.1.1 Configurations

Parameters	Value
CONFIG_MAX_CASTS	300
MAP_USE_PV	1
MAP_USE_SAF	0
MAPSCALE_LONGITUDE_LARGE	4
MAPSCALE_LONGITUDE_SMALL	1.33
MAPSCALE_LATITUDE_LARGE	4
MAPSCALE_LATITUDE_SMALL	1.33
MAPSCALE_PHI_LARGE	0.5
MAPSCALE_PHI_SMALL	0.1
MAPSCALE_AGE	10
MAP_P_EXCLUDE	700
MAP_P_DELTA	250



3.1.2 Results




Figure 13: Float 6901245. Location of the float profiles (red line with colored numbers) and the reference data selected for mapping (blue dots).







Figure 14: Float 6901245. Plot the original float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.








Figure 15: Float 6901245. Evolution of the suggested adjustment with time. The top panel plots the potential conductivity multiplicative adjustment. The bottom panel plots the equivalent salinity additive adjustment. The red line denotes one-to-one profile fit that uses the vertically weighted mean of each profile. The red line can be used to check for anomalous profiles relative to the optimal fit.







Figure 16: Float 6901245. The plot of calibrated float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.








Figure 17: Float 6901245. Plots of the evolution of salinity with time along with selected theta levels with minimum salinity variance.






Figure 18: Float 6901245. Plots include the theta levels chosen for calibration: Top left: Salinity variance at theta levels. Top right: T/S diagram of all profiles of Argo float. Bottom left: potential temperature plotted against pressure. Bottom right: salinity plotted against pressure.



The analysis of the θ -S diagram of profile segments deeper than 700 dbar (Figure 19) shows that the OW method was run where the θ -S relationship is the tightest.




Figure 19: Float 6901245. Uncalibrated float salinity profile (black lines) and mapped historical data (red lines) in the most uniform part of the θ -S curve.



4 Summary WMO 6901245 float

Float was deployed in the Catalan sub-basin, in the Mediterranean Sea. During its lifetime, the float passed in Algerian and Alboran sub basin where died. The most favorable water masses, which are useful for comparison with climatology is relatively stable intermediate and deep waters from around 700 m. The initial comparison between Argo float and reference data shows a very small salinity offset/drift. This float was not DMQC-ed before.

The OWC analysis showed a very small salinity offset/drift. Figure 15 indicates a small drifter after cycle 200. Figure 17 shows that the float salinity is quite constant on selected θ -levels until cycle 200 from which a very small drift is observed. The correction proposed by OW is quite small and below the Argo requested accuracy (0.01) for profile from 1 to 199, and just over 0.01 for others cycle. After several analyses, the last decision is that the salinity data of float WMO 6901245 is accurate and doesn't need a delayed mode correction. QC=1 is applied.

PSAL_ADJUSTED=PSAL from cycle 1 to 288

The quality flags applied are the following:

PSAL_ADJUSTED_QC='1' from cycle 1 to 288

The delayed-mode files (Dfiles) have been created accordingly and sent to the Coriolis GDAC.



5 Introduction WMO 6901251 Float

This report includes the delayed mode analysis performed for float 6901251. It was deployed in Mediterranean Sea (Algerian sub-basins) in July 2017 and after performed 205 cycles died. Before the analysis, real-time QC flags were visually inspected. The list of flags applied is QC=1 to all cycles, except for profile 69 that has position QC 4. Then, the satellite altimeter comparison plot between the sea surface height and dynamic height anomaly, constructed for this float by Ifremer, was analyzed. Plots of temperature and salinity time series and plots of temperature, salinity and density plotted against the nearby historical CTD profiles was generated. This visual analysis can help in detecting sensor salinity anomalies and spikes.

The reference dataset used is composed of the following CTD and Argo historical datasets:


CTD:

- CMEMS: INSITU_MED_TS_REP_OBSERVATIONS_013_041
- Coriolis: CTD_for_DMQC_2018V01
- Historical CTD profiles provided through personal contact

Argo:

ARGO_for_DMQC_2018V01

Float 6901251 is the Arvor float where the pressure sensor is auto corrected and no adjustment is required. The OWC was run to estimate a salinity offset and a salinity drift (Cabanes et al., 2016).





6 Quality Check of Argo WMO 6901251 Float Data

6.1 Verification of Real-time Mode QC flags

The list of flags applied to the float in real-time mode is as follows.

Cycle number:

1-205 PSAL QC=1

69 Position QC=4

6.2 Satellite Altimeter Report




Figure 20: Float 6901251. The comparison between the sea surface height (SSH) from the satellite altimetry and dynamic height anomaly (DHA) extracted from the Argo float temperature and salinity. The figure is created by the CLS/Coriolis and distributed by Ifremer (ftp://ftp.ifremer.fr/ifremer/argo/etc/argo-ast9-item13-AltimeterComparison/figures/).



6.3 Time Series of Argo Float Temperature and Salinity




Figure 21: Float 6901251. Time series of Argo float potential temperature (°C) on the left, and potential temperature profiles color-coded per cycle number on the right.




Figure 22: Float 6901251. Time series of Argo float potential salinity (PSS-78) on the left, and salinity profiles color-coded per cycle number on the right.

Two spikes were detected in salinity profile 159 at the pressure level of 9.8 dbar and 24.9 dbar (Figure 22). The quality flag associated to these salinity value was change to 4.



Before running the Owens and Wong method, referred to as OW hereafter, the theta-salinity (θ -S) diagram of the float is analyzed (Figure 23) and in particular the area where the θ -S relationship is the tightest (Figure 24). A potential salinity offset/drift is observed.




Figure 23: Float 6901251. θ -S diagram color-coded per cycle number.




Figure 24: Float 6901251. Area of the θ -S diagram (color-coded per cycle number) where the θ -S relationship is more uniform.



6.4 Comparison Between Argo Float and Climatology

Three salinity float profiles are selected to perform a comparison (in time and space) with the historical data. In figure 25, 26 and 27 each selected profile is compared with all reference data used in this analysis. The salinity float profile is depicted in black while other colors represent the salinity reference profiles. The red color means that the historical data are more recent with respect to the float ones, while magenta states that the float data are more recent than the historical ones (the maximal difference is 9 years). A time difference between 3 and 6, 6 and 9 and larger than 9 years is depicted in green, cyan and blue, respectively.




Figure 25: Float 6901251. Locations of the salinity float profile number 1 and historical CTD data (right panel) and the respective salinity profiles (left panel).




Figure 26: Float 6901251. Locations of the salinity float profile number 121 and historical CTD data (right panel) and the respective salinity profiles (left panel).






Figure 27: Float 6901251. Locations of the salinity float profile number 186 and historical CTD data (right panel) and the respective salinity profiles (left panel).

The comparison of these 3 selected salinity float profiles with the closest (in space and time) salinity reference profile in shown in Figures from 28 to 30. The agreement between the selected float salinity profiles and the historical salinity profiles is quite good in the intermediate layers where the comparison is useful for profiles 1 and 121. Figure 30 shows a small drift for profile 186 and the historical salinity profile.






Figure 28: Float 6901251. The salinity float profile number 1 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 29: Float 6901251. The salinity float profile number 121 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 30: Float 6901251. The salinity float profile number 186 (black dots) are compared to the nearest in space (top) and in time (botton) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.






Figure 31: Float 6901251. T/S diagram plotted with and data from WMO boxes of CTD reference data +/- 10° of latitude and longitude. The black and blue cycles indicate the first and the last Argo profile, respectively. Green symbols represent other Argo profiles from this float. The thin colours lines indicate the reference data.



7 Correction of WMO 6901251 Float Salinity Data

7.1.1 Comparison between Argo Float and CTD Climatology

7.1.1 Configurations

Parameters	Value
CONFIG_MAX_CASTS	300
MAP_USE_PV	1
MAP_USE_SAF	0
MAPSCALE_LONGITUDE_LARGE	4
MAPSCALE_LONGITUDE_SMALL	1.33
MAPSCALE_LATITUDE_LARGE	4
MAPSCALE_LATITUDE_SMALL	1.33
MAPSCALE_PHI_LARGE	0.5
MAPSCALE_PHI_SMALL	0.1
MAPSCALE_AGE	10
MAP_P_EXCLUDE	700
MAP_P_DELTA	250



7.1.2 Results




Figure 32: Float 6901251. Location of the float profiles (red line with colored numbers) and the reference data selected for mapping (blue dots).







Figure 33: Float 6901251. Plot the original float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.








Figure 34: Float 6901251. Evolution of the suggested adjustment with time. The top panel plots the potential conductivity multiplicative adjustment. The bottom panel plots the equivalent salinity additive adjustment. The red line denotes one-to-one profile fit that uses the vertically weighted mean of each profile. The red line can be used to check for anomalous profiles relative to the optimal fit.







Figure 35: Float 6901251. The plot of calibrated float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.








Figure 36: Float 6901251. Plots of the evolution of salinity with time along with selected theta levels with minimum salinity variance.






Figure 37: Float 6901251. Plots include the theta levels chosen for calibration: Top left: Salinity variance at theta levels. Top right: T/S diagram of all profiles of Argo float. Bottom left: potential temperature plotted against pressure. Bottom right: salinity plotted against pressure.



The analysis of the θ -S diagram of profile segments deeper than 700 dbar (Figure 38) shows that the OW method was run where the θ -S relationship is the tightest.




Figure 38: Float 6901251. Uncalibrated float salinity profile (black lines) and mapped historical data (red lines) in the most uniform part of the θ -S curve.



Comparison between Argo float under study and other Argo float in the 8 same area

Two floats, WMO 6901270 and WMO 6903248 (Figure 39), are selected to perform a comparison with the float under study, to obtain additional qualitative analysis.





Figure 39: Float 6901251. Trajectory of the floats used for the comparison.






Figure 40: Float 6901251. Comparison between float 6901251 (black line) and float 6903248 (red line), on the left. On the right zoom in the most uniform part of the θ -S curve and only for cycles from 269 to 300 (Catalan and Algerian sub basins).




Figure 41: Float 6901251. Comparison between float 6901251 (black line) and float 6901270 (red line), on the left. On the right zoom in the most uniform part of the θ-S curve.



9 Summary

Float was deployed in the Algerian sub-basin, in the Mediterranean Sea. During its lifetime, the float passed in Catalan and Alboran sub basin where died. The profile 69 ha QC=4 for position. Using interpolation method, we adjusted the position of this profile and applied QC=8. The most favorable water masses, which are useful for comparison with climatology is relatively stable intermediate and deep waters from around 700 m. The initial comparison between Argo float and reference data shows a potential salinity offset/drift. This float was not DMQC-ed before.

The OWC analysis showed a salinity offset/drift. Figure 34 indicates a potential drifter after cycle 120. Figure 36 shows that the float salinity is quite constant on selected θ -levels until cycle 120 from which a potential drift is observed. The float was compared with other two float in the same area. These comparisons, especially between 6901251 and 6901270 (figure 41), highlight a very small drift.

The correction proposed by OW is quite small and below the Argo requested accuracy (0.01) for profile from 1 to 120, and increasing for others cycle. The reference dataset is old and this can lead to an incorrect evaluation of the drift. After several analyses, the last decision is that the salinity data of float WMO 6901251 doesn't need a delayed mode correction. QC=1 is applied.

PSAL ADJUSTED=PSAL from cycle 1 to 205

The quality flags applied are the following:

PSAL_ADJUSTED_QC='1' from cycle 1 to 205 POSITION_QC='8' to cycle 69

The delayed-mode files (Dfiles) have been created accordingly and sent to the Coriolis GDAC.

10 References

Cabanes, C., Thierry, V., & Lagadec, C. (2016). Improvement of bias detection in Argo float conductivity sensors and its application in the North Atlantic. Deep-Sea Research Part I: Oceanographic Research Papers, 114, 128–136. https://doi.org/10.1016/j.dsr.2016.05.007