

Note of Delayed Mode Quality Control of Argo float WMO 6900804

For more detailed: Antonella Gallo agallo@ogs.it
ORCID ID: 0000-0002-8836-1550
27/08/2026

This note includes the results of OWC performed for the WMO 6900804 float. The reference dataset used is composed of the following CTD and Argo historical datasets:

CTD:

CMEMS:

- INSITU_MED_PHYBGCWAV_DISCRETE_MYNRT_013_035
- Coriolis: CTD_for_DMQC_2024V01
- Historical CTD profiles provided through personal contact

Argo:

- ARGO_for_DMQC_2025V03

Float 6900804 is the Apex float, for which no adjustment is required for surface pressure.

The OWC was run to estimate a salinity offset and a salinity drift (Cabanès et al., 2016).

Configurations

Parameters	Value
CONFIG_MAX_CASTS	300
MAP_USE_PV	1
MAP_USE_SAF	0
MAPSCALE_LONGITUDE_LARGE	4
MAPSCALE_LONGITUDE_SMALL	1.33
MAPSCALE_LATITUDE_LARGE	4
MAPSCALE_LATITUDE_SMALL	1.33
MAPSCALE_PHI_LARGE	0.5
MAPSCALE_PHI_SMALL	0.1
MAPSCALE_AGE	10
MAP_P_EXCLUDE	900
MAP_P_DELTA	100

OWC Results




Figure 1: Location of the float profiles (red line with colored numbers) and the reference data selected for mapping (blue dots).

6900804 uncalibrated float data (-) and mapped salinity (o) with objective errors




Figure 2: Plot the original float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.




Figure 3: Evolution of the suggested adjustment with time. The top panel plots the potential conductivity multiplicative adjustment. The bottom panel plots the equivalent salinity additive adjustment. The red line denotes one-to-one profile fit that uses the vertically weighted mean of each profile. The red line can be used to check for anomalous profiles relative to the optimal fit.

6900804 calibrated float data (-) and mapped salinity (o) with objective errors




Figure 4: The plot of calibrated float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.




Figure 5: Plots of the evolution of salinity with time along with selected theta levels with minimum salinity variance.




Figure 6: Plots include the theta levels chosen for calibration: Top left: Salinity variance at theta levels. Top right: T/S diagram of all profiles of Argo float. Bottom left: potential temperature plotted against pressure. Bottom right: salinity plotted against pressure.




Figure 7: Comparison between float 6900804 and historical CTD on the left and θ -S diagram color-coded per cycle number on the right, in the most uniform part of the θ -S curve.

Summary

Float WMO 6900804 was deployed in the Black Sea Sea. This float was DMQC-ed before. We applied OWC taking into account the high variability at the theta levels. The OWC analysis showed no salinity drift. Figure 5 shows that the float salinity is quite constant on selected θ -levels. The correction proposed by OWC is below the Argo required accuracy (0.01). Additional analyses (visual inspection of the deepest portion of the θ -S diagram and comparison of selected float salinity profiles with nearby historical CTD profiles) were performed to complement the OWC method and provide the best possible quality control assessment. The last decision is that the salinity data of float WMO 6900804 doesn't need a delayed mode correction applied to all cycles. QC 1 is applied.

PSAL_ADJUSTED=PSAL from cycle 1 to 168

The quality flags applied are the following:

PSAL_ADJUSTED_QC='1' from cycle 1 to 168

The delayed-mode files (Dfiles) have been created accordingly and sent to the Coriolis GDAC.

References

Cabanes, C., Thierry, V., & Lagadec, C. (2016). Improvement of bias detection in Argo float conductivity sensors and its application in the North Atlantic. Deep-Sea Research Part I: Oceanographic Research Papers, 114, 128–136. <https://doi.org/10.1016/j.dsr.2016.05.007>