


Delayed Mode Quality Control of Argo float WMO 6901252

Antonella Gallo

National Institute of Oceanography and Applied Geophysics - OGS
Borgo Grotta Gigante 42/C - 34010 - Sgonico (TS) – Italy
19/03/2021



Contents

- 1 Introduction..... 3**
- 2 Quality Check of Argo Float Data..... 4**
 - 2.1 Verification of Real-time Mode QC flags.....4
 - 2.2 Satellite Altimeter Report5
 - 2.3 Time Series of Argo Float Temperature and Salinity6
 - 2.4 Comparison Between Argo Float and Climatology 8
- 3 Correction of Salinity Data 14**
 - 3.1 Comparison between Argo Float and CTD Climatology.....14
 - 3.1.1 Configurations.....14
 - 3.1.2 Results.....15
- 4 Comparison between Argo float under study and other Argo float in the same area..... 22**
- 5 Summary 24**
- 6 References..... 24**

1 Introduction

This report includes the delayed mode analysis performed for float 6901252. It was deployed in Mediterranean Sea (Catalan sub-basins) in August 2018 and after performed 153 cycles died. Before the analysis, real-time QC flags were visually inspected. The list of flags applied is QC=1 to all cycles. Then, the satellite altimeter comparison plot between the sea surface height and dynamic height anomaly, constructed for this float by Ifremer, was analyzed. Plots of temperature and salinity time series and plots of temperature, salinity and density plotted against the nearby historical CTD profiles was generated. This visual analysis can help in detecting sensor salinity anomalies and spikes.

The reference dataset used is composed of the following CTD and Argo historical datasets:

CTD:

- CMEMS: INSITU_MED_TS_REP_OBSERVATIONS_013_041
- Coriolis: CTD_for_DMQC_2018V01
- Historical CTD profiles provided through personal contact

Argo:

- ARGO_for_DMQC_2018V01

Float 6901252 is the Arvor float where the pressure sensor is auto corrected and no adjustment is required. The OWC was run to estimate a salinity offset and a salinity drift (Cabanès et al., 2016).

2 Quality Check of Argo Float Data

2.1 Verification of Real-time Mode QC flags

The list of flags applied to the float in real-time mode is as follows.

Cycle number:

1-153 PSAL QC=1

2.2 Satellite Altimeter Report




Figure 1: Float 6901252. The comparison between the sea surface height (SSH) from the satellite altimetry and dynamic height anomaly (DHA) extracted from the Argo float temperature and salinity. The figure is created by the CLS/Coriolis and distributed by Ifremer (<ftp://ftp.ifremer.fr/ifremer/argo/etc/argo-ast9-item13-AltimeterComparison/figures/>).

2.3 Time Series of Argo Float Temperature and Salinity




Figure 2: Float 6901252. Time series of Argo float potential temperature (°C) on the left, and potential temperature profiles color-coded per cycle number on the right.




Figure 3: Float 6901252. Time series of Argo float potential salinity (PSS-78) on the left, and salinity profiles color-coded per cycle number on the right.

Two spikes were detected in salinity: one for profile 16 at the pressure level of 36 dbar and the second for profile 73 at the pressure level of 9 dbar (Figure 3). The quality flag associated to these salinity value was change to 4.

Before running the Owens and Wong method, referred to as OW hereafter, the theta-salinity (θ -S) diagram of the float is analyzed (Figure 4) and in particular the area where the θ -S relationship is the tightest (Figure 5). A very small salinity offset/drift is observed.




Figure 4: Float 6901252. θ -S diagram color-coded per cycle number.




Figure 5: Float 6901252. Area of the θ -S diagram (color-coded per cycle number) where the θ -S relationship is more uniform.

2.4 Comparison Between Argo Float and Climatology

Three salinity float profiles are selected to perform a comparison (in time and space) with the historical data. In figure 6, 7 and 8 each selected profile is compared with all reference data used in this analysis. The salinity float profile is depicted in black while other colors represent the salinity reference profiles. The red color means that the historical data are more recent with respect to the float ones, while magenta states that the float data are more recent than the historical ones (the maximal difference is 9 years). A time difference between 3 and 6, 6 and 9 and larger than 9 years is depicted in green, cyan and blue, respectively.




Figure 6: Float 6901252. Locations of the salinity float profile number 11 and historical CTD data (right panel) and the respective salinity profiles (left panel).




Figure 7: Float 6901252. Locations of the salinity float profile number 78 and historical CTD data (right panel) and the respective salinity profiles (left panel).




Figure 8: Float 6901252. Locations of the salinity float profile number 139 and historical CTD data (right panel) and the respective salinity profiles (left panel).

The comparison of these 3 selected salinity float profiles with the closest (in space and time) salinity reference profile is shown in Figures from 9 to 11. The agreement between the selected float salinity profiles and the historical salinity profiles is quite good in the intermediate and deep layers where the comparison is useful.






Figure 9: Float 6901252. The salinity float profile number 11 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.


Float 6901252 - profile 78 (05-Aug-2019) and nearest (in space) ctd (01-Jul-2010)



Float 6901252 - profile 78 (05-Aug-2019) vs nearest (in space) ctd (01-Jul-2010)



Float 6901252 - profile 78 (05-Aug-2019) and nearest (in time) ctd (30-Sep-2013)



Float 6901252 - profile 78 (05-Aug-2019) vs nearest (in time) ctd (30-Sep-2013)




Figure 10: Float 6901245. The salinity float profile number 78 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.




Figure 11: Float 6901252. The salinity float profile number 248 (black dots) are compared to the nearest in space (top) and in time (bottom) reference profile (red dots). The locations of the two profiles and their distance is given in the left panel.




Figure 12: Float 6901252. T/S diagram plotted with and data from WMO boxes of CTD reference data +/- 10° of latitude and longitude. The black and blue cycles indicate the first and the last Argo profile, respectively. Green symbols represent other Argo profiles from this float. The thin colour lines indicate the reference data.

3 Correction of Salinity Data

3.1 Comparison between Argo Float and CTD Climatology

3.1.1 Configurations

Parameters	Value
CONFIG_MAX_CASTS	300
MAP_USE_PV	1
MAP_USE_SAF	0
MAPSCALE_LONGITUDE_LARGE	4
MAPSCALE_LONGITUDE_SMALL	1.33
MAPSCALE_LATITUDE_LARGE	4
MAPSCALE_LATITUDE_SMALL	1.33
MAPSCALE_PHI_LARGE	0.5
MAPSCALE_PHI_SMALL	0.1
MAPSCALE_AGE	10
MAP_P_EXCLUDE	700
MAP_P_DELTA	250

3.1.2 Results




Figure 13: Float 6901252. Location of the float profiles (red line with colored numbers) and the reference data selected for mapping (blue dots).

6901252 uncalibrated float data (-) and mapped salinity (o) with objective errors




Figure 14: Float 6901252. Plot the original float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.




Figure 15: Float 6901252. Evolution of the suggested adjustment with time. The top panel plots the potential conductivity multiplicative adjustment. The bottom panel plots the equivalent salinity additive adjustment. The red line denotes one-to-one profile fit that uses the vertically weighted mean of each profile. The red line can be used to check for anomalous profiles relative to the optimal fit.

6901252 calibrated float data (-) and mapped salinity (o) with objective errors




Figure 16: Float 6901252. The plot of calibrated float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.




Figure 17: Float 6901252. Plots of the evolution of salinity with time along with selected theta levels with minimum salinity variance.




Figure 18: Float 6901252. Plots include the theta levels chosen for calibration: Top left: Salinity variance at theta levels. Top right: T/S diagram of all profiles of Argo float. Bottom left: potential temperature plotted against pressure. Bottom right: salinity plotted against pressure.

The analysis of the θ -S diagram of profile segments deeper than 700 dbar (Figure 19) shows that the OW method was run where the θ -S relationship is the tightest.




Figure 19: Float 6901252. Uncalibrated float salinity profile (black lines) and mapped historical data (red lines) in the most uniform part of the θ -S curve.

4 Comparison between Argo float under study and other Argo float in the same area

Two floats, WMO 6902803 and WMO 6902773 (Figure 20), are selected to perform a comparison with the float under study, to obtain additional qualitative analysis.




Figure 20: Float 6901252. Trajectory of the floats used for the comparison.




Figure 21: Float 6901252. Comparison between float 6901252 (black line) and float 6903252 (red line), on the left. On the right zoom in the most uniform part of the θ -S curve and only for cycles from 192 to 288 (Catalan and Algerian sub basins).




Figure 22: Float 6901252. Comparison between float 6901252 (black line) and float 6902771 (red line), on the left. On the right zoom in the most uniform part of the θ -S curve and only for cycles from 114 to 154 (Catalan and Algerian sub basins).

5 Summary

Float was deployed in the Algerian sub-basin, in the Mediterranean Sea. During its lifetime, the float passed in Algerian sub basin where died. The most favorable water masses, which are useful for comparison with climatology is relatively stable intermediate and deep waters from around 700 m. The initial comparison between Argo float and reference data shows a potential salinity offset/drift. This float was not DMQC-ed before.

The OWC analysis showed a salinity offset/drift. Figure 15 indicates a potential drifter. Figure 17 shows that the float salinity is quite constant on selected θ -levels but at beginning and from cycle 123 from which a potential drift is observed. The float was compared with other two float in the same area. These comparisons, especially between 6901252 and 6902803 (figure 21), highlight a very small drift.

The correction proposed by OW is quite small and below the Argo requested accuracy (0.01) for profile from 1 to 123, and slightly exceeds 0.01 for the other cycles. The reference dataset is old and this can lead to an incorrect evaluation of the drift. After several analyses, the last decision is that the salinity data of float WMO 6901251 doesn't need a delayed mode correction. QC=1 is applied. The DMQC analysis will be repeated with a new reference dataset.

PSAL_ADJUSTED=PSAL from cycle 1 to 153

The quality flags applied are the following:

PSAL_ADJUSTED_QC='1' from cycle 1 to 153

The delayed-mode files (Dfiles) have been created accordingly and sent to the Coriolis GDAC.

6 References

Cabanes, C., Thierry, V., & Lagadec, C. (2016). Improvement of bias detection in Argo float conductivity sensors and its application in the North Atlantic. *Deep-Sea Research Part I: Oceanographic Research Papers*, 114, 128–136. <https://doi.org/10.1016/j.dsr.2016.05.007>