

# Note of Delayed Mode Quality Control of Argo float WMO 6903239

For more detailed: Antonella Gallo [agallo@ogs.it](mailto:agallo@ogs.it)

ORCID ID: 0000-0002-8836-1550

10/10/2026

This note includes the results of OWC performed for the WMO 6903239 float. The reference dataset used is composed of the following CTD and Argo historical datasets:

CTD:

CMEMS:

- INSITU\_MED\_PHYBGCWAV\_DISCRETE\_MYNRT\_013\_035
- Coriolis: CTD\_for\_DMQC\_2024V01
- Historical CTD profiles provided through personal contact

Argo:


- ARGO\_for\_DMQC\_2025V03

Float 6903239 is the Arvor float, where the pressure sensor is auto corrected and no adjustment is required. The OWC was run to estimate a salinity offset and a salinity drift (Cabanès et al., 2016).

## Configurations


| Parameters               | Value |
|--------------------------|-------|
| CONFIG_MAX_CASTS         | 300   |
| MAP_USE_PV               | 1     |
| MAP_USE_SAF              | 0     |
| MAPSCALE_LONGITUDE_LARGE | 4     |
| MAPSCALE_LONGITUDE_SMALL | 1.33  |
| MAPSCALE_LATITUDE_LARGE  | 4     |
| MAPSCALE_LATITUDE_SMALL  | 1.33  |
| MAPSCALE_PHI_LARGE       | 0.5   |
| MAPSCALE_PHI_SMALL       | 0.1   |
| MAPSCALE_AGE             | 10    |
| MAP_P_EXCLUDE            | 700   |
| MAP_P_DELTA              | 250   |

OWC Results




**Figure 1:** Location of the float profiles (red line with colored numbers) and the reference data selected for mapping (blue dots).

6903239 uncalibrated float data (-) and mapped salinity (o) with objective errors




**Figure 2:** Plot the original float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.

**6903239 potential conductivity (mmho/cm) multiplicative correction  $r$  with errors**




**6903239 vertically-averaged salinity (PSS-78) additive correction  $\Delta S$  with errors**




**Figure 3:** Evolution of the suggested adjustment with time. The top panel plots the potential conductivity multiplicative adjustment. The bottom panel plots the equivalent salinity additive adjustment. The red line denotes one-to-one profile fit that uses the vertically weighted mean of each profile. The red line can be used to check for anomalous profiles relative to the optimal fit.





6903239 calibrated float data (-) and mapped salinity (o) with objective errors




**Figure 4:** The plot of calibrated float salinity and the objectively estimated reference salinity at the 10 float theta levels that are used in calibration.



**Figure 5:** Plots of the evolution of salinity with time along with selected theta levels with minimum salinity variance.



**Figure 6:** Plots include the theta levels chosen for calibration: Top left: Salinity variance at theta levels. Top right: T/S diagram of all profiles of Argo float. Bottom left: potential temperature plotted against pressure. Bottom right: salinity plotted against pressure.



**Figure 7:** Comparison between float 6903239 – cycles 1-251 - and historical CTD on the left and  $\theta$ -S diagram color-coded per cycle number on the right, in the most uniform part of the  $\theta$ -S curve.

## Summary

Float WMO 6903239 was deployed in the Tyrrhenian sub-basin of the Mediterranean Sea. During its lifetime, it later moved into the Algerian sub-basin. This float wasn't DMQC-ed before. We applied the OWC method taking into account the deepest profiles. The OWC analysis showed a significant salinity drift. From profile 252 data became bad and unadjustable. Additional analyses (visual inspection of the deepest portion of the  $\theta$ -S diagram and comparison of selected float salinity profiles with nearby historical CTD profiles) were performed to complement the OWC method and provide the best possible quality control assessment. The last decision is that the salinity data of float WMO 6903239 needs a delayed mode correction. QC 1 is applied to cycle 1-251. Bad data and QC 4 to cycles 251-385

PSAL\_ADJUSTED=PSAL +  $\Delta$ S from cycle 1 to 251

PSAL\_ADJUSTED=PSAL from cycle 252 to 385

The quality flags applied are the following:

PSAL\_ADJUSTED\_QC='1' from cycle 1 to 251

PSAL\_ADJUSTED\_QC='4' from cycle 252 to 385

The delayed-mode files (Dfiles) have been created accordingly and sent to the Coriolis GDAC.

## References

Cabanes, C., Thierry, V., & Lagadec, C. (2016). Improvement of bias detection in Argo float conductivity sensors and its application in the North Atlantic. *Deep-Sea Research Part I: Oceanographic Research Papers*, 114, 128–136. <https://doi.org/10.1016/j.dsr.2016.05.007>